

SafetyGel®

Liquid-applied waterproofing covering for wet rooms floors and/or walls system (kit)

Performance of the product following ETA 26/0375 EAD 030352-00-0503:

Vapour permeability	$s_d=3,77$ m (vapour brake)
Water tightness	Watertight
Crack bridging ability	0,75 mm (category 2)
Bond strenght	$\geq 0,9$ Mpa (category 2)
Water tightness around penetrations	Watertight
Resistance to temperature	$\geq 0,5$ Mpa (category 2)
Resistance to water	$\geq 0,5$ Mpa (category 2)
Resistance to alkalinity	$\geq 0,5$ Mpa (category 2)
Repairability	Passed 1,1 Mpa (category 2)

 ETA-Danmark A/S Søborg Plads 1 DK-2150 Nordhavn Tel. +45 72 24 59 00 Internet www.eta-danmark.dk	Authorised and notified according to Article 20 of the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011	
European Technical Assessment ETA-26/0375 of 2026/06/22		
I General Part		
Technical Assessment Body issuing the ETA and designated according to Article 29 of the Regulation (EU) No 305/2011: ETA-Danmark A/S		
Trade name of the construction product:	Litokol SafetyGel	
Product family to which the above construction product belongs:	Liquid applied watertight covering kit for wet room floors and walls	
Manufacturer:	Litokol Lab S.p.A. Via G. Falcone 13/1 42048 Rubiera (R.E.) Italy	
Manufacturing plant:	Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera (RE) Italy	
This European Technical Assessment is issued in accordance with Article 95(4) of Regulation (EU) 2024/3110, on the basis of:	EAD 030352-00-0503: Liquid applied watertight covering kit for wet room floors and/or walls	